FJDynamics

DelGeo



E600

The E600 is an industrial-grade controller featuring IP67 protection. With a powerful 2.2 GHz 8-core processor and a vibrant 5.5-inch display, the E600 ensures smooth operation and exceptional user experience, making it an ultimate field partner for faster and smarter surveying jobs.

Hold Comfortably, Work Anywhere
Feature an ergonomic design that ensures a comfortable grip for extended use. You can also use it smoothly even if you're wearing gloves or your hands are wet, giving you more flexibility in challenging environments.

CPU

Powerful Hardware Combo
Deliver fast, reliable performance with a 2.2GHz 8-core processor. With 4GB of RAM and 64GB of ROM, you'll have plenty of space for multitasking and storage, keeping up with your busiest project days.

5.5 inch

Excellent Display Interaction
Come standard with a 5.5-inch high-definition display (720x1440 resolution) for clear visuals. The 5-point capacitive touchscreen ensures smooth responsiveness, easily recognizing different finger gestures for quick operation.

IP67

Strong Protection Performance
Come with IP67 rating, work against dust, water, and accidental drops from heights of up to 1.8m, making it a rugged companion for outdoor environments. This durability ensures performance stays sharp no matter the challenge you're facing in the project.

QUICK SPECS

GENERAL

OS	Android 11
CPU	8-core at 2.2GHz
RAM	4GB
ROM	64GB
Display	5.5 inch screen, 5-point capacitive touch
NFC	Supporting agreements: ISO14443A/B, ISO15693
	NFC Read Range: 0–5 cm
Camera	13MP rear camera with high brightness LED flash
Battery	7700 mAh
Audio	Bottom stereo speakers
	Volume 90dB+3dB (test distance 10cm) with1 MIC
Keyboard	Number/Letter Keyboard
Dimension (HxWxD)	221×77.7×16 mm
Weight	355 g

COMMUNICATION

Bluetooth	Bluetooth5.0 (BLE)
Wi-Fi	IEEE 802.11 a/b/g/n/ac 2.4G/5G dual frequency
Network Protocol	TDD-LTE, FDD-LTE, WCDMA, GSM, CDMA

INTERFACE

SIM Card Slot	2 Nano SIM card slots
SD Card Slot	1 Micro SD card slot (up to 256GB)
USB	USB Type-C interface, supporting OTG
	Fast charging 5V/9V 1.67A

PERFORMANCE

Working Temperature	-20°C to 55°C
Storage Temperature	-30°C to 70°C
Humidity	5%–95%
ESD Protection	+16kV Air Discharge, ±8kV Contact Discharge
IP Rating	IP67
Drop Resistance	1.8 m free drop onto concrete with 6 sides

*All specifications are subject to change without notice.

CE FC R 211-250118

GET IT ON Google Play 2 NFC 5.5 inch IP67



CREATE FOR A BETTER WORLD

Copyright © FJDynamics. All rights reserved.

DelGeo

ПОСТАВКА ГЕОДЕЗИЧЕСКОГО ОБОРУДОВАНИЯ